



T7 Plus

integrated terminal with
one-touch operation



Lead with the next-generation T7 terminal:

- Easy-loading clamshell design printer
- Globally certified for secure transactions including EMV and PED approved
- Single function keys for simple transaction initiation



T7 Plus

integrated terminal with one-touch operation



Simple One-touch Operation

The T7 Plus from Hypercom® features an extended keypad, providing easy initiation of a wide range of transactions and functions at the press of a single button. A range of different display types are available to support standard, graphical and ATM-style operation.

A Secure Investment

The T7 Plus provides internal PIN security with support for connecting an external PIN entry device, and is certified to global and local standards including EMV and PED approval. Software compatible with earlier Hypercom T7 series models, the T7 Plus extends the life of investment and reduces certification and training requirements.

Printing Performance

The quiet thermal printer has a larger paper roll capacity, and the semi-transparent clamshell alerts operators to low paper prior to running out. The enhanced printer design allows paper rolls to be simply dropped in place without feeding through slots and rollers. The T7 Plus is an all-in one device ideal for meeting the demands of everyday transactions.

For more information about the T7 Plus,
please visit: www.hypercom.com or email info-emea@hypercom.com

Hypercom EMEA Ltd

Unit 2, Woking Eight, Forsyth Road, Woking, Surrey GU21 5SB England
Tel. +44.1483.718600 Fax. +44.1483.718601

Specifications:

Keypad

35 elastomeric keys (standard);
3 screen-addressable keys (optional)
6 ATM-style keys (optional)

Display

2 x 20 character LCD (standard)
4 x 20 character LCD (optional)
32 x 140 pixel graphic display (optional)
64 x 128 pixel ATM-style graphic display (optional)
LED backlight

Printer

Drop-in loading, thermal technology
384 dots per line resolution
Paper roll: 57mm wide, 80mm diameter

Chip Card Reader/Writer

ISO7816; 4 SIM Sockets

Magnetic Stripe Reader

Tracks 1, 2 (standard)
Tracks 1, 2, 3 (optional)

Communications

Up to 2400bps including V.23, V.22bis, V.22 and V.21 Synchronous (SDLC) & Asynchronous or
Up to 56 K with FastPOS as fallback
Peripheral Ports: 1 RS422/485 for PIN Pad
RS232 with optional powerout
Hypercom LAN RS485

Security

Physical: Intrusion detector & secure CPU
Key Management:
Master/session keys (12) or DUKPT
Encryption: PIN ANSI 9.8, MAC ANSI 9.9,
3 DES MAC ANSI 9.9

Memory

1 MB (standard); 2 MB (optional)

Certifications

Certified to global standards including
EMV Level 1, EMV Level 2 & PED approved

Power

AC 85-250 V, 50/60 Hz
DC 24 V, 1 A

Environment

Temperature 0-45°C/32-113°F
Humidity max 85%, non-condensing
ESD 12,000 volts

Colours

Black (standard),
A full colour range is available for
volume requests

Weight

680 grams

Footprint

254mm x 132mm x 635mm

Specifications subject to change without notice